



NCR Cash4all™

Specification

MORE ↗ **RESULTS**

Product dimensions	
Height With standard topper Standard topper Small topper	2,600mm (102.4") 830mm (32.7") 70mm (2.7")
Width	1,000mm (39.4")
Depth	1,040mm (40.9")
Weight Without weatherised Personas 77	175kg (386lbs) min
Fascia	Aperture to fit weatherised Personas 77
Installation	Suitable for interior or exterior locations

Features & options

Self-coloured, insulated fibreglass to resist vandalism/wear and tear and designed for maximum durability in extreme conditions

Power protection device

Anti-ram raid option

Integrated bollard option

Internal door alarm option

Configurable lock options

Additional features

Heating & cooling systems where necessary

Weather protection option for servicing/replenishment

Advertising capability with graphics/lighting options

Customisable options to suit individual customer design requirements

- Colour, decals, wraps, panels

Accommodates weatherised Personas 77

Front access unit Standard Personas 77 displays, EPP keyboard, IMCRW card reader, printer, UL291 security, primary lock, processor, memory and fascia colour customisation features are available

Dispenser

1, 2, or 3 denomination options with bunch, retract and purge capability for exterior placements

1, 2, 3, or 4 denomination options with bunch, retract and purge capability for interior placements

NCR multimedia cassette with 295mm (11.6") capacity

Full Fluiditi™ solution available including penetration and explosion detect options

Accessibility

Subject to customer compliance with NCR Site Preparation and Installation Guidelines, Cash4all complies with **ADAAG sections 4.34.2, 4.34.3 and 4.34.4** (as amended through September 2002). Of the remaining portions of ADAAG specifically addressed to automated teller machines, section 4.34.1 addresses the route on which the product is placed and not aspects of the product itself and section 4.34.5 is a performance standard that does not specify how to achieve or measure compliance and therefore NCR does not offer guidance as to such compliance.

• **AS3769-1990 - Australian Standard for Accessibility** - with minor exceptions, the Cash4all produced for sale in Australia complies with this standard

• **Access to ATMs: UK Design Guidelines 2002** - with minor exceptions, the Cash4all produced for sale in the UK conforms with these guidelines

• **CAN/CSA B651.1-01** - with minor exceptions, the Cash4all produced for sale in Canada complies with this standard

Communication options

Visa II dial-up

TCP/IP

Leased line

56k V. 90 internal mode

Wireless communications enabled*

Environmental

The complete Cash4all hardware with water management system satisfies the UL291 rain water ingress test requirements

Temperature

-35°C to +50°C (31°F to +122°F) (ambient) with appropriate heating/cooling systems where necessary

Change rate: 10°C per hour

Dew point temperature restriction: 26°C max

Humidity

20% to 80%

Acoustics

Sound power 55dBA idle, 60dBA operating

Sound pressure 55dBA operating

* Where available

Advertising capability



Wrap



Customer interface



Weather protection for cash



NCR Corporation, 1700 South Patterson Boulevard, Dayton, Ohio, 45479, USA

www.ncr.com

www.self-service-touchpoints.com

NCR continually improves products as new technologies and components become available. NCR, therefore, reserves the right to change specifications without prior notice.

© 2004 NCR Corporation

All features, functions and operations described herein may not be marketed in all parts of the world. Consult your NCR representative for the latest information.

SP 2467