



NCR EasyPoint™ 53

Specification

MORE ↗ RESULTS

Product dimensions	
Height	614mm (24.2")
Width	470mm (18.5")
Depth	470mm (18.5")
Weight 1 hopper combination lock 2 hopper combination lock	52kg (115lbs) 55kg (121lbs)
Installation	Suitable for interior locations

Customer interface

Display

196mm (7.7") VGA colour flat panel screen

8 tactile function display keys

Keyboard

Secure EPP (Encrypting PIN Pad)¹: supports Triple DES and Remote Key Management

Card reader

DIP

Smart DIP²: supports smart cards

Dispenser

1 or 2 denominations

Printer

Receipt printer

40 column graphics thermal printer

Capacity up to 2,350 transactions, 145mm (5.7") receipts

Security

EPP (Encrypting PIN Pad)¹: certified as meeting the requirements of ISO 9564-1, ISO 13491-1, and ISO 13491-2

Smart DIP card reader²: certified to EMV 3.1.1 Level 1, certified GIECB

Safe

Business hours

Accessibility

Subject to customer compliance with NCR Site Preparation and Installation Guidelines, the EasyPoint 53 complies with **ADAAG sections 4.34.2, 4.34.3 and 4.34.4** (as amended through September 2002). Of the remaining portions of ADAAG specifically addressed to automated teller machines, section 4.34.1 addresses the route on which the product is placed and not aspects of the product itself and section 4.34.5 is a performance standard that does not specify how to achieve or measure compliance and therefore NCR does not offer guidance as to such compliance.

• AS3769-1990 -

Australian Standard for Accessibility - with minor exceptions, the EasyPoint 53 produced for sale in Australia complies with this standard

• Access to ATMs: UK Design Guidelines 2002

- with minor exceptions, the EasyPoint 53 produced for sale in the UK conforms with these guidelines

• CAN/CSA B651.1-01 -

- with minor exceptions, the EasyPoint 53 produced for sale in Canada complies with this standard

Additional Features

Electronic journaling

Pedestal

Communication options*

Visa II dial-up

TCP/IP

Leased line

56k V. 90 internal modem

Environmental

Temperature

10°C to 40°C (50°F to 104°F)

Humidity

20% to 80%

Acoustics

Sound power 55dBA idle, 60dBA operating

Sound pressure 55dBA operating

Power requirements

120v to 240v
50Hz to 60Hz

Electronic Platform

PC based with Intel Pentium® processor

* Dependent on software application

