



NCR Personas™ 79

Specification

MORE ↗ RESULTS

Product dimensions	
Height	1,667mm (65.6")
Width	600mm (23.6")
Depth	992mm (39.1")
Weight	626kg (1,380lbs)
Installation	Front or rear lobby access

Customer interface

Display

381mm (15") CRT colour screen

Optional touchscreen

8 tactile function display keys

Keyboard

Secure EPP (Encrypting PIN Pad)¹: supports Triple DES and Remote Key Management

Card reader

IMCRW (Integrated Motorised Card Reader)²: option to support smart cards

Public/private audio

High quality stereo sound, or sound jack with volume control

Deposit

Cash Acceptor

Accepts and validates up to 60 notes per transaction

Up to 50 note denominations per template

Remote download of currency templates

Scalable storage up to 8,000 notes

Escrow capable of returning notes to customer

ECB Article 6 compliant

iTRAN 1000 Check Processor

Cheque and credit slip processing

True MICR read of E13B or CMC7 code line

High quality front and rear imaging of documents

Rear endorsement printing either single line or multi-line

High capacity storage in 3 selectable power stacking bins

CAR/CAV/LAR options

Separate enclosures for cash and cheques

Printers

Receipt printer

40 column graphics thermal printer including cheque image printing

Optional sideways feature allows 80 column x 20 row mini-statement

Journal printer

40 column graphics thermal or dot matrix printer

Security

EPP (Encrypting PIN Pad)¹: certified as meeting the requirements of ISO 9564-1, ISO 13491-1 and ISO 13491-2

IMCRW card reader²: certified EMV 3.1.1 and EMV 4.0 Level 1 certified GIECB, ZKA

Optional fraud countermeasures include ECD (Enhanced Card Drive or 'Jitter') and CROPF (Card Return on Power Fail)

Safe

UL291 Level 1

Environmental

Temperature

10°C to 40°C (50°F to 104°F)


Humidity

20% to 80%

Acoustics

Sound power 55dBA idle, 60dBA operating

Sound pressure 55dBA operating



NCR Corporation, 1700 South Patterson Boulevard, Dayton, Ohio, 45479, USA

www.ncr.com

www.self-service-touchpoints.com

NCR continually improves products as new technologies and components become available. NCR, therefore, reserves the right to change specifications without prior notice.

© 2004 NCR Corporation

All features, functions and operations described herein may not be marketed in all parts of the world. Consult your NCR representative for the latest information.

SP 2423